

FORM FINISHER

SERIES QAD

Manual form finisher for ironing men's and women's jackets and overcoats.

Features and strengths

Available in two versions:

QAD-1 - Without a built-in generator-to be connected to a centralised steam plant

QAD-2 - With a built-in electric steam generator, meeting the PED standards - capacity 20 liters, 10 - 13,5 kW

- Body rotating 360°, height 127 cm (upon request, 147 cm)
- Front and back paddle with manual closing
- Manual opening of shoulders, based on size
- Mini-computer for programming the timing of steam, steam with blowing and blowing - 9 programs - piece metre, user friendly software
- Wood sleeve stretchers and stainless steel clamps for closing of vents
- Blowing motor at 1,3 kW - 1,7 hp
- Manually adjustable air-blowing quantity
- Manual extra steam and air-blowing using computer
- Steam consumption: 15 kg/h
- Productivity - approximately 40 pcs/h



TYPE		QAD 1	QAD 2
ELECTRIC CONNECTIONS			
Supply voltage	-	230 - 400 V / 3 Ph / 60 Hz	
Boiler	lt	-	20
Boiler resistance	kW	-	8 - 10 - 13
Fan motor	kW	1,3	
Pump motor	kW	-	0,5
Water inlet	Ø	-	3/4"
Steam inlet	Ø	3/8"	-
Condensate return	Ø	3/8"	-
Boiler discharge	Ø	-	1/2"
Steam pressure	bar	4,5	
Net weight	kg	95	135
Gross weight	kg	135	175
Shipping dimensions W x D x H	mm	1280 x 640 x 2040	
OVERALL DIMENSIONS			
Width	mm	620	
Depth	mm	1260	
Height	mm	1750	1900

Different voltage and frequency specifications on request

ASSEMBLY AND PREPARATION OF THE MACHINE



DESCRIPTION	mm		mm		DIMENSION
WATER INLET	A1	110	A2	145	3/4"
ELECTRIC POWER	B1	450	B2	55	
CONDENSATION RETURN	C1	70	B2	55	3/8"
STEAM	F1	185	B2	55	3/8"
BOILER DISCHARGE	G1	70	G2	865	1/2"

UniMac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.