

VACUUM AND/OR VACUUM-BLOWING IRONING TABLE

SERIES 388

Features and strengths

- Heated to keep work surface dry
- Utility shape for multipurpose operation
- Integrated vacuum fan holds the garment in place and dry the fabric after pressing

Options

- Built-in boiler 5 liters, 4 kW for independent unit, complete of electric steam iron
- Swinging arm with heated sleeve arm
- Steam gun
- Lighting device
- Steam iron suspension
- Electric steam iron group
- Anti shine Teflon Shoe
- Vacuum and blowing motor 0,80 hp
- Iron rest



TYPE		388/A	388/AC	388/S	388/SC	388/SMC	388/SM
ELECTRIC CONNECTIONS							
Standard voltage 230 V / 1 Ph / 50 Hz	kW	2		2			2
400 V / 3 Ph / 50 Hz	kW		7		7	8	
Other voltages available on request Vacuum and blowing fan power	kW	0,60	0,60	0,60	0,60	0,75	0,77
STEAM, AIR AND WATER CONNECTIONS							
Steam inlet	inch	1/4"		1/4"			1/4"
Steam outlet	inch	3/8"		3/8"			3/8"
Steam supply	bar	3,5		3,5			3,5
Steam consumption	kg/h	3		3			3
Compressed air inlet	inch			1/4"	1/4"		
Compressed air consumption	bar			25	25		
Compressed air supply	bar			5	5		
Water inlet	inch		1/2"		1/2"	1/2"	
Water drainage	inch		1/2"		1/2"	1/2"	
Vacuum outlet	mm	100	100	100	100	100	100
Boiler capacity	lt		5		5	5	
SHIPPING DETAILS							
Packing type		Pallet + carton box; 1650 x 550 x 1000 mm					
Shipping dimensions	mm	2000 x 2300 x 1600					
Net weight	kg	70	110	80	110	110	80
Gross weight	kg	90	130	100	130	130	100

UniMac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.