

# VACUUM-BLOWING IRONING BOARD

## SERIES 2000

**Modular ironing table with vacuum and air-blowing.**

### Features and strengths

- Independent manual adjustment of vacuum and air-blowing
- Mobile pedal unit with adjustable depth, with possibility of right or left ironing
- Infinite height adjustment, garment holders with adjustable height
- Electrically heated (2000E) or cold (2000C) bucks, easily interchangeable (see page 20), special bucks upon request
- 4-layer padding with pure silicon foam
- Vertical air discharge chimney
- High-depression vacuum motor at 0,6 kW - 0,8 hp
- Automatic change of vacuum and blowing from buck to arm

### Options

- Mobile right or left stainless steel arm with ergonomic moulding
- Lighting device and iron trolley adjustable in height and depth
- Additional iron-rest, adjustable in height and depth, for right point ironing
- LED computer mod. COLOMBO with electronic inverter for control of vacuum and blowing quantities and table functions
- Condensation separator group, with electric-steam or steam iron, or with temperature control using high-precision electronic display (see catalogue for irons)
- Anti-shine shoe in PTFE-aluminium or stainless steel
- Air-water spray gun
- Steam or air/steam gun group, stain-removing form in stainless steel

### NEW

- Built-in electric steam generator - capacity 5 liters - 4 kW, meets PED standards
- No delay in the switch from vacuum to blowing, thanks to the action of pneumatic cylinders, for companies without compressed air, electric switching also available




| TYPE  |     | 2000 with boiler unit      | 2000 without boiler unit |
|---|-----|----------------------------|--------------------------|
| <b>ELECTRIC CONNECTIONS</b>                               |     |                            |                          |
| Supply voltage  | -   | 230 - 400 V / 3 Ph / 50 Hz | 230 V / 1 Ph / 50 Hz     |
| Surface height adjustment                                 | mm  | 720 - 950                  |                          |
| Buck resistance   | kW  | 0,8                        |                          |
| Boiler resistance   | kW  | 3                          | -                        |
| Ironing unit resistance                                   | kW  | 0,8                        |                          |
| Vacuum unit motor   | kW  | 0,6                        | 0,6                      |
| Pump motor  | Ø   | 0,45                       | -                        |
| Water inlet   | Ø   | 1/2"                       | -                        |
| Boiler discharge  | bar | 3/8"                       | -                        |
| Air pressure  | kg  | 2,5                        |                          |
| Net weight  | kg  | 145                        | 120                      |
| Gross weight  | kg  | 170                        | 145                      |
| <b>OVERALL DIMENSIONS</b>                                 |     |                            |                          |
| Width   | mm  | 1700                       |                          |
| Depth   | mm  | 650                        |                          |
| Height  | mm  | 900                        |                          |
| Different voltage and frequency specifications on request |     |                            |                          |




## MAIN BUCK TABLES (MM)


2002E




2003E



2004E - 1970



2005E



2006E



UniMac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.