

1. Hard-mounted Washer Extractors

UW105, UW130, UW160, UW200

Features and Benefits

- UniLinc control for 300 G extraction (UW105, 130, 160) and 200 G extraction (UW200)
- Water saving and reduce cycle times rinsing technology
- Industrial construction is built to run 24/7
- Dual drain
- Liquid soap connection
- Electric or steam heating
- Overdimensioned steel frame
- Stainless steel drum and tub
- Perforated cylinder ribs maximize wash action

Options

- M30 Control (programmable microcomputer) - (UW105 130)
- 5 cup soap dispensers



| SPECIFICATIONS | | UW105 | | UW130 | | UW160 | | UW200 | |
|--------------------------------------|--------------------|---------------------------|--|-----------------------|--|---------------------------|--|---------------------------|--|
| Capacity - kg (lb) | | 45 (105) | | 56 (130) | | 68 (160) | | 91 (200) | |
| Cylinder Diameter - mm (in) | | 914 (36) | | 1067 (42) | | 1067 (42) | | 1067 (42) | |
| Cylinder Depth - mm (in) | | 686 (27) | | 622 (24 1/2) | | 762 (30) | | 953 (37 1/2) | |
| Cylinder Volume - liters (cu. ft.) | | 450 (15.9) | | 555 (19.6) | | 682 (24.1) | | 852 (30.1) | |
| Width - mm (in) | | 1090 (40 3/25) | | 1171 (46 1/8) | | 1171 (46 1/8) | | 1171 (46 1/8) | |
| Depth - mm (in) | | 1435 (56 1/2) | | 1384 (54 1/2) | | 1524 (60) | | 1715 (67 1/2) | |
| Height - mm (in) | | 1755 (69 2/25) | | 1932 (76 1/20) | | 1932 (76 1/8) | | 1932 (76 1/8) | |
| Door Opening Size - mm (in) | | 533 (21) | | 630 (24 13/16) | | 630 (24 13/16) | | 630 (24 13/16) | |
| Door Bottom to Floor - mm (in) | | 713 (28 3/32) | | 758 (29 13/16) | | 758 (29 13/16) | | 758 (29 13/16) | |
| Motor Size - kW (HP) | | 5.6 (7.5) | | 7.5 (10) | | 7.5 (10) | | 7.5 (10) | |
| Control Options | | M30 UniLinc™ | | M30 UniLinc™ | | UniLinc™ | | UniLinc™ | |
| Total # of Speeds | | M Sp V Sp | | M Sp V Sp | | V Sp | | V Sp | |
| | | 6 8 | | 6 8 | | 8 | | 8 | |
| Cylinder Speed RPM (G-Force) | Gentle Wash | 28 (.40) 28 (.40) | | 26 (.40) 26 (.40) | | 26 (.40) 26 (.40) | | 26 (.40) 26 (.40) | |
| | Distribution | 70 (2.5) 70 (2.5) | | 65 (2.5) 65 (2.5) | | 65 (2.5) 65 (2.5) | | 65 (2.5) 65 (2.5) | |
| | Very Low Extract | 230 (27) 230 (27) | | 213 (27) 213 (27) | | 213 (27) 213 (27) | | 213 (27) 213 (27) | |
| | Low Extract | 443 (100) 443 (100) | | 410 (100) 410 (100) | | 410 (100) 410 (100) | | 366 (80) 366 (80) | |
| | Medium Extract | 626 (200) 626 (200) | | 579 (200) 579 (200) | | 579 (200) 579 (200) | | 458 (125) 458 (125) | |
| | High Extract | — 700 (250) | | — 648 (250) | | 648 (250) 648 (250) | | 502 (150) 502 (150) | |
| | Very High Extract | — 766 (300) | | — 710 (300) | | 710 (300) 710 (300) | | 579 (200) 579 (200) | |
| | Ultra High Extract | — — | | — — | | — — | | — — | |
| Drain Diameter - mm (in) | | 1 @ 76 (3) 2 @ 76 (3) | | 1 @ 76 (3) 2 @ 76 (3) | | 2 @ 76 (3) 2 @ 76 (3) | | 2 @ 76 (3) 2 @ 76 (3) | |
| Steam Connection - mm (in) | | 13 (1/2) | | 19 (3/4) | | 19 (3/4) | | 19 (3/4) | |
| Water Inlet Connection - mm (in) | | 2 @ 19 (3/4) 4 @ 19 (3/4) | | 2 @ 25 (1) | | 2 @ 25 (1) + 2 @ 19 (3/4) | | 2 @ 25 (1) + 2 @ 19 (3/4) | |
| Shipping Dimensions - mm (in) | Width | 1097 (43 3/16) | | 1250 (49 3/16) | | 1250 (49 3/16) | | 1250 (49 3/16) | |
| | Depth | 1570 (61 13/16) | | 1646 (64 13/16) | | 1646 (64 13/16) | | 1836 (72 1/4) | |
| | Height | 1763 (69 3/8) | | 1941 (76 3/8) | | 1941 (76 3/8) | | 1941 (76 3/8) | |
| Net Weight - kg (lb) | | 771 (1700) | | 925 (2040) | | 939 (2070) | | 980 (2160) | |
| Standard Shipping Weight - kg (lb) | | 794 (1750) | | 953 (2100) | | 966 (2130) | | 1007 (2220) | |
| Slat Crate Shipping Weight - kg (lb) | | 862 (1900) | | 1025 (2260) | | 1039 (2290) | | 1084 (2390) | |
| Agency Approvals* | | cULus, CE | | cULus, CE | | cULus, CE | | cULus, CE | |

UniMac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.