

1. Hard-mounted Washer Extractors

UW45, UW65, UW85

Features and Benefits

- Stainless steel drum and tub
- Perforated cylinder ribs maximize wash action
- UniLinc control for 400 G extraction (UW45, 65) and 300 G extraction (UW85)
- Water saving and reduce cycle times rinsing technology
- Industrial construction is built to run 24/7
- Dual drain (UW85)
- Liquid soap connection
- Electric or steam heating
- Overdimensioned steel frame

Options

- M30 Control (programmable microcomputer)
- 5 cup soap dispensers



SPECIFICATIONS		UW45			UW65			UW85	
Capacity - kg (lb)		21 (45)			28 (65)			37 (85)	
Cylinder Diameter - mm (in)		787 (31)			787 (31)			914 (36)	
Cylinder Depth - mm (in)		422 (16 5/8)			561 (22 1/8)			559 (22)	
Cylinder Volume - liters (cu. ft.)		207 (7.3)			275 (9.7)			368 (13)	
Width - mm (in)		867 (34 1/8)			867 (34 1/8)			1019 (40 1/8)	
Depth - mm (in)		1126 (44 21/64)			1266 (49 53/64)			1308 (51 1/2)	
Height - mm (in)		1642 (64 5/8)			1642 (64 5/8)			1717 (67 19/32)	
Door Opening Size - mm (in)		452 (17 51/64)			452 (17 51/64)			533 (21)	
Door Bottom to Floor - mm (in)		713 (28 3/32)			713 (28 3/32)			713 (28 3/32)	
Motor Size - kW (HP)		3.7 (5)			3.7 (5)			5.6 (7.5)	
Control Options		M30		UniLinc™	M30		UniLinc™	M30	UniLinc™
Total # of Speeds		L Sp	M Sp	V Sp	L Sp	M Sp	V Sp	M Sp	V Sp
		5	6	9	5	6	9	6	8
Cylinder Speed RPM (G-Force)	Gentle Wash	30 (0.40)	30 (0.40)	30 (0.40)	30 (0.40)	30 (0.40)	30 (0.40)	28 (.40)	28 (.40)
		42 (.78)	42 (.78)	42 (.78)	42 (.78)	42 (.78)	42 (.78)	39 (.78)	39 (.78)
	Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	70 (2.5)	70 (2.5)
	Very Low Extract	248 (27)	248 (27)	248 (27)	248 (27)	248 (27)	248 (27)	230 (27)	230 (27)
	Low Extract	477 (100)	477 (100)	477 (100)	477 (100)	477 (100)	477 (100)	443 (100)	443 (100)
	Medium Extract	—	674 (200)	674 (200)	—	674 (200)	674 (200)	626 (200)	626 (200)
	High Extract	—	—	754 (250)	—	—	754 (250)	—	700 (250)
	Very High Extract	—	—	826 (300)	—	—	826 (300)	—	766 (300)
Ultra High Extract	—	—	954 (400)	—	—	954 (400)	—	—	
Drain Diameter - mm (in)		76 (3)			76 (3)			1 @ 76 (3)	2 @ 76 (3)
Steam Connection - mm (in)		13 (1/2)			13 (1/2)			13 (1/2)	
Water Inlet Connection - mm (in)		2 @ 19 (3/4)	2 @ 19 (3/4)	4 @ 19 (3/4)	2 @ 19 (3/4)	2 @ 19 (3/4)	4 @ 19 (3/4)	2 @ 19 (3/4)	4 @ 19 (3/4)
Shipping Dimensions - mm (in)	Width	945 (37 13/64)			945 (37 13/64)			1097 (43 3/16)	
	Depth	1370 (53 13/16)			1370 (53 13/16)			1570 (61 13/16)	
	Height	1650 (65)			1650 (65)			1763 (69 3/8)	
Net Weight - kg (lb)		490 (1080)			499 (1100)			757 (1670)	
Standard Shipping Weight - kg (lb)		508 (1120)			522 (1150)			780 (1720)	
Slat Crate Shipping Weight - kg (lb)		567 (1250)			581 (1280)			848 (1870)	
Agency Approvals*		ETL, CE			ETL, CE			cETLus, CE	

UniMac preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding.